

PILLOW BLOCK BEARING; Model: RSAO 2 7/16; p/n RSAO 2 7/16; Mfg Fafnir/ Timken

- **Performance:** An advanced fluid end design gives exceptionally smooth Triplex performance. This unique design facilitates fast inspection and easy servicing.
- **Flexibility:** Compact engineering provides higher efficiency in less space. The pump's light weight and flexible design make it easily adaptable to a variety of rig configurations. This provides flexibility as drilling requirements and conditions change.
- **Fluid End Modules:** NOV offers a choice of fluid end modules and valve covers for every P Series pump model to select the fluid end module that exactly matches drilling requirements. All pump models can be equipped with either the standard or premium forged, two-piece interchangeable fluid modules.

Bore Size d 2 7/16 in 61.9 mm
Bearing Number GN207KRRB
Inside Ring Outside Diameter 0.937 in 23.8 mm
Dimension B1 3.126 in 79.4 mm
Dimension T 2.000 in 50.8 mm
Series Medium-Duty
Weight 35.591 lb 16.144 Kg

Seal Type Shroud Seal

Shaft Height H 104.78 mm 4.125 in

Total Length L 349.2 mm 13.748 in

Total Width A 4.000 in 101.6 mm

Bolt Hole Spacing J 285.8 mm 11.252 in

Bolt Hole Width N 22.2 mm 0.874 in

Bolt Hole Length N1 34.9 mm 1.374 in

Base Height H1 38.1 mm 1.500 in

Total Height H2 186.5 mm 7.343 in

Dimension L1 116.4 mm 4.583 in

Inside Ring Width B N/A

Center of Bearing from End S 31 mm 1.220 in